



DATE: 29/01/2022







DATE: 29/01/2022

APPLICANT : VIBEZ PUNE

ATTENTION : MR. KARAN

SAMPLE DESCRIPTION: ONE PIECE OF SUBMITTED KNITTED LONG SLEEVE T-SHIRT SAMPLE IN COLOR MARKED AS WHITE / BLUE.

WASH CARE INSTRUCTION: MACHINE WASH AT 30°C, FLAY DRY

| SAMPLE RECEIVED DATE / TEST STARTED DATE: 24/01/2022 | | |
|--|--|--|
| : | | |
| : | | |
| : | | |
| : | | |
| : 100 % COTTON | | |
| : WHITE / BLUE | | |
| : | | |
| : | | |
| : | | |
| : | | |
| : M | | |
| | | |

TEST CONDUCTED AS PER THE REQUEST OF THE APPLICANT. FOR FURTHER DETAILS, PLEASE REFER TO ENCLOSED PAGES.

AUTHORIZED BY

SUNDARMURTHY KRISHNAN DIRECTOR (CALIDATEX)





DATE: 29/01/2022

1] DIMENSIONAL STABILITY TO WASHING AFTER ONE WASH (ISO 6330)

IHTM – FRONT LOADING IFB WASHING MACHINE, MACHINE WASH AT 30°C WITH 2KG LOAD IN SURF EXCEL MATIC DETERGENT FOLLOWED BY FLAT DRY.

| | <u>ORIGINAL (CM)</u> | AFTER ONE WASHES (CM) | DIMENSIONAL <u>CHANGE</u> <u>(%)</u> | REQUIREMENT |
|-----------------------|----------------------|--------------------------|--|--------------------|
| NECK WIDTH | 16.5 | 16.3 | -1.2 | -5/+2% |
| ARMHOLE | 27.3 | 26.8 | -1.8 | |
| CHEST | 48.1 | 46.8 | -2.7 | |
| SHOULDER | 32.0 | 31.8 | -0.6 | |
| воттом | 49.1 | 48.7 | -0.8 | |
| CENTER BACK LENGTH | 68.6 | 67.7 | -1.3 | |
| SLEEVE LENGTH | 75.0 | 74.6 | -0.5 | |
| SIDE SEAM | 46.7 | 46.3 | -0.9 | |

2] COLOR FASTNESSS TO WASHING (ISO 105 C 06)

30 MINUTES WASH AT 30° C WITH 4 GMS SURF EXCEL MATIC DETERGENT, 1 GM SODIUM PERBORATE TETRAHYDRATE WITH 10 STEEL BALLS.

| | <u>RESULT</u> | REQUIREMENT |
|----------------|---------------|--------------------|
| COLOUR CHANGE | 4 | 4 |
| COLOR STAINING | | |
| COTTON | 4 | 3-4 |
| POLYESTER | 4-5 | |
| SELF STAINING | 4-5 | 4-5 |

3] FIBRE CONTENT [ISO 1833] 🖾

| | RESULT | REQUIREMENT |
|--------|--------|-------------|
| COTTON | 100 % | * |





DATE: 29/01/2022

4] FABRIC WEIGHT- [ISO 3801] - AFTER WASH 🛛

| | RESULT | REQUIREMENT |
|-------------------|--------|--------------------|
| GM/M ² | 192.9 | * |
| OZ/SQ. YD | 5.7 | |

5] ICI PILLING RESISTANCE- [ISO 12945-1]-18000 REV.- AFTER WASH 🛛

| | <u>RESULT (BLUE & WHITE)</u> | REQUIREMENT |
|------------|----------------------------------|--------------------|
| LENGTH – 1 | 4 | |
| WIDTH – 1 | 4 | |
| AVERAGE | 4 | 3-4 |

⊠ - THESE TESTS ARE UNDER OUR SCOPE OF ACCREDITATION AS PER ISO/IEC 17025:2017

-----END OF THE TEST REPORT -----

SAMPLE NOT DRAWN BY CALIDATEX; RESULTS RELATE ONLY TO THE SAMPLE TESTED. THIS TEST REPORT SHALL NOT BE PUBLISHED IN ANY FORM WITHOUT THE EXPLICIT WRITTEN CONSENT OF THE CALIDATEX.